

Tips on BRICKFORM® Blush-Tone Acid Stain™ Application

This is abbreviated information taken from the BRICKFORM Blush-Tone Acid Stain Technical Information Sheet and MSDS. Read both references before attempting to use this product. BRICKFORM strongly recommends testing an area for results before total application.

DO

PREPARATION

Concrete must be cured at least 28 days.
Remove all coatings and any material that will keep the stain from reacting.
Protect adjacent areas from over-spray, runoff and tracking.

APPLICATION

Use a pump-type garden sprayer for large areas.
Use sponges or brushes for small or tight areas.
Always brush back into stained areas to avoid overlap.

CLEANUP

Allow the stain to dry overnight before residue removal.
Always neutralize the rinse-water.

SEALING

Use a high-quality sealer such as BRICKFORM Gem-Seal, high-gloss sealer, Master-Seal, slip-resistant sealer, or Satin-Seal, water-based, semi-gloss sealer.

MAINTENANCE

Inspect annually for signs of worn sealer and reapply as necessary.

DO NOT

PREPARATION

Do not use acid to clean the concrete.
Do not use Jade, Turquoise or Olive on slag concrete or in areas of dripping water or hydrostatic pressure.

APPLICATION

Do not use sprayers with metal parts or spray tips.
Do not allow material onto areas where color is not desired.
Do not allow material to run off into plant life.
Do not allow material to puddle.

CLEANUP

Do not allow rinse water to runoff into adjacent areas.
Do not let rinse water runoff into plant life.

SEALING

Do not apply a sealer until the concrete has completely dried after rinsing.
Do not apply sealer until a test sample area has been approved.

MAINTENANCE

Do not reapply a sealer until all efflorescence and deleterious materials have been removed.

WARRANTY

This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven to be defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability. **Continue on pg. 2**

SAFE HANDLING INSTRUCTIONS

• **WARNING** • **CORROSIVE** Contains Acid. **DO NOT TAKE INTERALLY.** Avoid contact with skin and eyes and clothing. Do not breathe vapor or mist. Wear acid vapor mask (NIOSH/MSHA TC 23C approved), goggles, rubber gloves, protective clothing and chemical-resistant apron and boots. Use good hygiene when handling this product and wash and bathe after each use. Be sure to wash clothing after each use. Close container after each use.