



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Phone: 410-675-2100 or 800-543-3840

Revised: 5/02/2006

DAP® Fast 'N Final® Lightweight Spackling

- One step – no sanding
- No cracking
- Fast drying
- Interior/exterior use

Packaging: 4 eaches-1 fluid ounce packs, 1/2 pint tub, 1 pint tub, 1 quart tub, 1 gallon tub, 273 ml, 473 ml, 946 ml, 3.8 L

Color: White

UPC Numbers: 12149, 12140, 12141, 12142, 12143, 23030, 23050, 71354, 23090

Company Identification:

Manufacturer: DAP Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.

Order Information: 800-327-3339

Fax Number: 410-534-2650

Also, visit the DAP website at www.dap.com.

Product Description:

DAP® Fast 'N Final® Lightweight Spackling may be used to spot patch and repair holes, cracks, crevices and dents in interior and exterior surfaces such as drywall, plaster, wood and stucco. Its advanced, lightweight formula is easy to apply and offers long lasting adhesion and durability. Will not crack or shrink. Paintable.

Suggested Uses:

Ideal for filling holes, cracks and defects:

- Drywall/Plaster
- Wood
- Stone
- Stucco

Surface Preparation & Application:

- Surface must be clean, dry and free of foreign material.
- Mix gently before use. Apply with a clean putty knife.
- For a smoother finish, dip putty knife into water and lightly smooth spackling.
- One application is usually sufficient for small repairs. For repairs deeper than 1/4", apply two or more layers allowing to dry between applications.
- May be painted within minutes with a latex paint.
- If sanding is desired, or if an oil-based paint is to be used, allow to dry thoroughly approximately 2-4 hours. Wet sanding is recommended to avoid generation of dust.
- Clean tools immediately with water.

For Best Results:

- Do not apply when temperatures are below 50° F.
- Do not apply outside if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior applications, always topcoat with a good quality paint.
- Do not use for tuck pointing applications on brick.
- For larger areas to be patched on bare concrete, use a latex fortified Portland cement-based dry mix.

Physical & Chemical Characteristics:

Consistency:	Thick Paste
Vehicle:	Latex Polymer
Volatile:	Water
Filler:	Inert Filler
Odor:	Slight Acrylic
Weight/Gallon:	4.0 ± .3 pounds
Solids:	75 ± 1% by weight
Application Temperature:	50° F Minimum
Service Temperature:	-20°F to 150°F
Shelf Life:	1 Year
Freezing:	Freeze/Thaw Stable 5 Cycles at 0°F
Drying Time:	2 to 4 hours depending on temperature, relative humidity and depth of fill.
Painting:	Takes either oil or latex-base paint
MSDS No.:	000 10410 001

Clean Up:

Wash tools immediately after use with water. Be sure container lid is closed and tightly sealed. Store in a cool, dry place.

Safety:

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at www.dap.com or by calling 888-DAP-TIPS.

Satisfaction Guaranteed:

If you are not satisfied with this product's performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.