



# Product Technical Data Sheet

## Miracote<sup>®</sup> Multipurpose Protective Coating (MPC)

### 1. PRODUCT DESCRIPTION

#### A. COMPOSITION

Miracote Protective Coating is a polymerized cementitious protective coating. It consists of a unique rubber-like polymer liquid mixed at the time of application with a cement aggregate blend. The material is applied in multiple coats by brush, roller, trowel or spray to a typical thickness of 3/32" (2,4mm). It can be applied over almost any clean, sound surface (concrete, block, tile, metal, masonry, wood, etc.) for a number of different floor, wall and roof uses.

Important characteristics of Miracote Protective Coating are its extraordinary adhesion coupled with its ability to withstand prolonged pedestrian and vehicular traffic. In these respects, the material is far superior to conventional cementitious coatings.

MPC provides a tough water-retardant coating which substantially reduces or prevents water penetration, freeze-thaw scaling and concrete carbonation. It is a "breathable" coating which releases normal entrapped vapor without loosening or blistering. MPC is available in two basic colors – white and natural cement. A compatible acrylic topcoat, an optional application, is available in eighteen additional colors; plus black, white and custom matched colors. Also, available in three grades of texture-smooth, regular and coarse aggregate.

#### B. TYPICAL USES

- Concrete exterior restoration
- Parking structure protection
- Sidewalk resurfacing
- Wall refinishing and installation coating
- Stadium renovation
- Swimming pool walkways
- Balcony deck surfacing
- Concrete and masonry water tank linings

#### C. ADVANTAGES AND LIMITATIONS

##### ADVANTAGES:

1. Excellent adhesion and weathering resistance.
2. Long wearing under traffic.
3. Retards water and salt penetration.
4. Resists ultraviolet degradation from long-term exposure to sunlight.
5. Environmentally safe – entirely water-based.
6. Slip resistant underfoot.
7. Moderate cost

##### LIMITATIONS:

1. May reflect working concrete cracks.
2. Do not install in freezing weather.
3. Minor shade variation may occur with natural cement color material.
4. Not suitable for us in areas where acids are spilled.
5. Efflorescence can develop as a result of the migration of water and can result in the failure of substrate or bond or discoloration of the surface.

### 2. TYPICAL PHYSICAL PROPERTIES at 75°F (24°C)

#### A. Adhesion

ASTM C882, Type I 515 psi

#### B. Absorption

Weight gain by 4" coated concrete cube after 21 days water immersion Canadian Mortgage & Housing Corp. <2%  
ME 8211-09230 (2" material cube, immersion 48hrs) 8.79%

#### C. Freeze-Thaw

#### D. Weathering

ASTM G23 (Weatherometer) Method 1 procedure, 60 cycles. No visible degradation

#### E. Hydrocarbon Substances Resistance

ASTM D1308 (Spot Open Test) 21 days repeated re-application of gasoline, motor oil SAE-10, jet fuel  
No softening or attack

#### F. Resistance to Wind-Driven Rain

Fed. Spec. TT-C-558 (8hrs) & TT-P-0035 (24hrs)  
At 5" water pressure and 60 gal/hr water flow  
No water or dampness noted on back of test panels

#### G. Compressive Strength

ASTM C109 2,440 psi

#### H. Tensile Strength

ASTM C190 430 psi

#### I. Shore Hardness

ASTM D2240 Durometer "A" – 82

#### J. Impact Resistance

MIL-D-3134, Para. 4.7.3 No cracking or detachment  
(2 lb steel ball dropped from 8-ft height onto coated steel plate)

#### K. Water Vapor Permeability

E96 1.96 perms/inches

#### L. Flammable Properties

ASTM E84 (Steiner Tunnel Test) Flame Spread – 4  
Smoke Density – 0

#### M. Potable Water Compatibility

Approved - U.S. Environmental Protection Agency  
Criteria and Standards Division office of Drinking Water  
(Complies with NSF/ANSI 61)

#### N. Fire Resistance

UL790 Complies as Class A

### 3. INSTALLATION

- A. Prepare surfaces by removal of dirt, foreign matter plus patching in accordance with manufacturer's recommendations.
- B. Apply first coat of Miracote.
- C. Apply following coats (one or two depending on service conditions/requirements) by broom, roller, brush or spray. Finish to specified texture.
- D. Color Finish (optional) – apply acrylic color finish, when specified, in two coats by roller, brush or spray.

**CAUTION:** Do not install Miracote in cold weather (i.e. below 50°F/10°C) or when rainfall can be expected prior to material setting.

### 4. PRODUCT AVAILABILITY

Crossfield Products Corp. maintains offices and/or factories at all addresses listed below. Factory Trained Contractors are established in all major trading areas in the United States, Canada and various European, Latin American and Far East nations.

### 5. CLEANING

Cleaning and disinfecting compounds and cleaning techniques can affect the color, gloss, texture and performance of the system. As a precautionary step, Crossfield recommends that the end-user test their cleaning and disinfecting compounds on a sample or on a small, out of the way finished area, utilizing the intended cleaning technique prior to cleaning the entire surface area. If no deleterious effects are observed, the procedure can be continued. If the cleaning and disinfecting compounds or cleaning techniques damage the system, modification of the cleaning material or techniques will be required. Contact your Representative for additional information.

### 6. MAINTENANCE

For maximum sheen and cleanability, floor should be routinely treated with conventional maintenance finish followed by ordinary buffing.

### 7. SPECIFICATION ASSISTANCE

Consult Crossfield Products Corp. for specification assistance, detailing, etc. This consultation is highly recommended prior to specification.

### 8. TESTING

The technical data contained herein is the result of tests made in Crossfield's laboratories or in independent laboratories using small scale equipment, following generally accepted trade practices. Although this information is believed to be true and accurate, the use of different equipment for testing under dissimilar conditions or the testing of samples produced under dissimilar conditions may develop substantially different results.

### LIMITED WARRANTY

NO WARRANTY SHALL BE EFFECTIVE UNTIL THE TERMS AND CONDITIONS OF SALE SET FORTH IN CROSSFIELD PRODUCTS CORP. INVOICES ARE MET.

Crossfield Products Corp. warrants to the purchaser of its products that such products are free from manufacturing defect. Crossfield does not warrant or guarantee the workmanship performed by any person or firm installing its products. Crossfield's obligation under this warranty is limited solely to the original purchaser and solely to the remedy of replacement in kind of any product which Crossfield sold which may prove defective in manufacture within one year from date of installation, provided said product was stored correctly and installed within the product's shelf life, by the original purchaser and which Crossfield's examination shall disclose to Crossfield's satisfaction to be thus defective.

IN NO EVENT SHALL CROSSFIELD PRODUCTS CORP. BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. THIS WARRANTY IS EXPRESSLY GIVEN IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR USE AND ALL OTHER OBLIGATIONS OR LIABILITIES ON CROSSFIELD'S PART, AND WE NEITHER ASSUME NOR AUTHORIZE ANY PERSON OR PERSONS TO ASSUME FOR US ANY OTHER LIABILITY IN CONNECTION WITH SALE OF A CROSSFIELD PRODUCT. THIS WARRANTY SHALL NOT APPLY TO ANY OF CROSSFIELD'S PRODUCTS, WHICH HAVE BEEN SUBJECT TO ADULTERATION, ALTERATION ABUSE OR MISUSE. CROSSFIELD PRODUCTS CORP. MAKES NO WARRANTY WHATSOEVER IN RESPECT TO ACCESSORIES, PARTS OR MATERIAL NOT SUPPLIED BY CROSSFIELD PRODUCTS CORP., WHICH ARE USED IN CONNECTION WITH ITS PRODUCTS. THE TERM "ORIGINAL PURCHASER" IN THIS WARRANTY MEANS THAT PERSON, CORPORATION OR ENTITY TO WHOM CROSSFIELD PRODUCTS CORP. SOLD ITS PRODUCTS. ANY ACTION TO ENFORCE ANY WARRANTY OR FOR BREACH OF CONTRACT OR ARISING OUT OF ANY CLAIM AGAINST CROSSFIELD PRODUCTS CORP. SHALL BE COMMENCED AND MAINTAINED ONLY IN A COURT OF COMPETENT JURISDICTION IN THE CONTINENTAL UNITED STATES OF AMERICA. THE PURCHASER ACCEPTS THESE TERMS AND CONDITIONS, AND HEREBY EXPRESSLY WAIVES ANY CLAIM TO ADDITIONAL DAMAGES.

CAUTION: ALWAYS KEEP OUT OF THE REACH OF CHILDREN.



#### MIRACOTE PRODUCT LINE Crossfield Products Corp.

<b>West Coast Office</b> 3000 E. Harcourt Street Rancho Dominguez, CA Roselle Park, NJ 90221 310-886-9100 310-886-9119 fax	<b>East Coast Office</b> 140 Valley Road    07204 908-245-2800 908-245-0659 fax
--	--

[www.miracote.com](http://www.miracote.com)