

MATCRETE
**RHINO
GRIP**



SLIP-RESISTANT ADDITIVE

Matcrete **RHINO GRIP** Slip-Resistant Additive is a micronized polymer for addition to sealers for slip-resistance and fine texturing. Due to its low oil absorption and high solvent resistance, it will stir easily into most solvent-based coatings with minimal effect on the coating's viscosity. Its low density allows it to stay well suspended.

FEATURES

- For inclined driveways, garages, steps, patios and pool decks.
- Spherical-shaped particles allow easy cleaning of the surface.
- Spherical-shaped particles provide a smoother feel under foot when used on pool decks and patios.

BENEFITS

- Puts "bite" on concrete surfaces.
- Slip-resistance.
- Easy addition into sealers.
- Good chemical and abrasion resistance.
- Good universal compatibility without viscosity effects.

LIMITATIONS

Rhino Grip will increase the coefficient of friction on the surface of a coating, but due to its small particle size, the coating that this is added to should be considered.

PACKAGE SIZES/COVERAGE

- 4 ounces of Rhino Grip per gallon of sealer.
- 1 pound of Rhino Grip per five gallons of sealer.
- Also available in 100 pound drums.

INSTRUCTIONS FOR USE

Add the proper amount of Rhino Grip to the sealer and mix with a mechanical paddle mixer. Rhino Grip should be added slowly and evenly. Mix well for 5 to 10 minutes and apply with a pump-up sprayer (use proper tip for spray applications) or apply with a roller. Do not re-roll wet areas.

Note: Some low-pressure pump-up sprayers may not be able to dispense sealers with Rhino Grip.

CAUTION!

Rhino Grip is not hazardous and does not contain silica, but should be treated as a nuisance dust while incorporating it into its intended vehicle. It is recommended that when mixing into unfamiliar coatings, a small test batch and application be made.

**KEEP OUT OF REACH OF CHILDREN.
USE ONLY WITH ADEQUATE VENTILATION.**

SLIP-RESISTANT BUT NOT NON-SKID

TECHNICAL BULLETIN

RHINO GRIP-2/06

MATCRETE · 1495 Hudson Avenue · Ontario, CA · 91764

PHONE (800)777-7063 · FAX (909)635-0165

www.matcrete.com