

# **SURTEC<sup>®</sup>, Inc. Surface Technology**

1880 N. MACARTHUR DR.

TRACY, CA 95376

Telephone (209) 820-3700

Fax (209) 820-3793

## **SAFE STRIP T**

ST-850

### **VISCOUS PAINT & SOLVENT SEAL STRIPPER**

#### **DESCRIPTION:**

SAFE STRIP T was developed to provide a user-safe and environment-safe stripper for solvent base seals, paints, and water base seals. The thickened formula helps to increase dwell time to vertical or sloped sealed surfaces. SAFE STRIP T contains no methylene chloride, is not flammable, and is without the other problems associated with petroleum solvents.

SAFE STRIP T is safe to use on all masonry surfaces such as cement, quarry tile, ceramic tile, terrazzo or other masonry surfaces; it may also be used to strip wood floors down to bare wood. It can be applied to horizontal surfaces, or used in a dip tank. Test in an inconspicuous area; if in doubt, consult SURTEC.

#### **DIRECTIONS:**

For stripping seals, SAFE STRIP T should not be diluted. Apply SAFE STRIP T using a mop, sprayer or spread out using a deck brush. Work small areas at a time. Do not walk in areas where SAFE STRIP T is on the floor, as it is very slippery underfoot. Allow from at least 15 minutes to 60 minutes dwell time, occasionally scrubbing or agitating with a floor buffer with a brush (Zim Grit brush for concrete) or deck brush. Before picking up the stripper solution, check a small area (<1 square foot) to ensure the seal has been completely removed. If not, allow SAFE STRIP T to dwell longer with occasional scrubbing. When ready for removal, add water to the surface, scrub into the stripper, and pick up or vacuum the stripper solution using a wet-dry vacuum. For masonry surfaces, scrub the stripped floor with SURTEC HC-150 diluted 4 oz. per gallon of water, followed by thoroughly rinsing the floor with water. For wood surfaces, mop the floor several times using a tightly wrung mop with SURTEC SURCO diluted 4 ounces per gallon. Allow floor to dry completely before applying seal or finish.

#### **SPECIFICATIONS:**

COLOR: ..... Lt. straw  
ODOR: ..... Sweet, citrus  
HMIS RATING ..... Health =2 Flammability = 2 Physical Hazard = 0  
FLASH POINT: ..... 140° F.  
DILUTION RATE: ..... Ready to use  
METHOD OF APPLICATION: ..... Solvent proof pump-up sprayer, mop  
COVERAGE: ..... 60 to 100 square feet per gallon  
DWELL TIME: ..... 15 to 60 minutes or more, depending on type and amount of  
..... coating to be stripped.  
VISCOSITY: ..... 1000 cps. (Brookfield RVF-100, Spindle # 3, 50 rpm)  
BIODEGRADABLE: ..... Yes  
pH: ..... N/A  
DETERGENT TYPE: ..... Nonionic  
SPECIFIC GRAVITY: ..... 0.97  
DENSITY: ..... 8.1 pounds per gallon  
SOLUBILITY IN WATER: ..... Less than 1% (hard, soft and/or deionized water)  
SHELF LIFE: ..... Minimum 1 year from date of sale  
FREEZE/THAW STABILITY: ..... Minimum 3 cycles (A.S.T.M. Test D-3209-82)  
CONTAINER SIZES AVAILABLE: ..... 4 x 1 gallon jugs  
..... 5 gallon pail  
..... 55 gallon drum

rev. 7/10/03

SURTEC warrants this product to be of consistent quality. SURTEC'S warranty is limited to the replacement of product proven defective. The user assumes all other risks and liabilities resulting from the use of this product. If you have any questions, please call SURTEC at (510) 582-7800.